

# Material Safety Data Sheet

To comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

## CLOR-N-OIL 20, 50, 100 or 500 PCB SCREENING KIT

### Section I --- Manufacturer

**Manufacturer's Name:**

Dexsil Corporation

**Emergency Telephone Number:**

USA (800) 424-9300 (CHEMTREC)

INT'L (202) 483-7616

**Address:**

One Hamden Park Drive  
Hamden, CT 06517

**Telephone Number:**

(203) 288-3509

**Date Prepared:** 08-16-01

**Date Reviewed:** 08-16-01

### Section II --- Identification of Hazardous Ingredients

The CLOR-N-OIL PCB Screening Kit consists of one test tube containing two ampules, one test tube containing two ampules and an aqueous solution, and another separate ampule. All versions of Clor-N-Oil (20, 50, 100, 500) contain less than or equivalent amounts of the compounds listed below.

<u>Component</u>	<u>Ingredients</u>	<u>TLV/(PEL)</u>	<u>CAS#</u>	<u>Concentration</u>
<i>Ampule 1</i> (gray color)	Sodium (dispersed in oil)	2 mg/m <sup>3</sup> /(2 mg/m <sup>3</sup> )	7440-23-5	0.36% (1.78%)
<i>Ampule 2</i> (blue-dot)	Naphthalene (in Diglyme Sol'n)	50 mg/m <sup>3</sup> /(50 mg/m <sup>3</sup> ) 5 ppm	91-20-3 111-96-6	0.49% (1.97%)
<i>Ampule 3</i> (colorless)	Mercuric Nitrate (in water)	0.1 mg/m <sup>3</sup> /(0.1 mg/m <sup>3</sup> )	10045-94-0	0.06% (7.82%)
<i>Ampule 4</i> (red-green)	Ethanol	1900 mg/m <sup>3</sup> /(1900 mg/m <sup>3</sup> )	00064-17-5	4.07%
<i>Ampule 5</i> (colorless)	Organo-Sulfur Cmpd.	1 mg/m <sup>3</sup> /(1 mg/m <sup>3</sup> )	Proprietary	5.18%
<i>Aqueous Sol'n</i>	Sulfuric Acid (in water)	1 mg/m <sup>3</sup> /(1 mg/m <sup>3</sup> )	7664-93-9	1.58% (79.19%)

### **Section III --- Physical Characteristics**

<b><u>Property</u></b>	<b><u>Ampule1</u></b>	<b><u>Ampule2</u></b>	<b><u>Ampule3</u></b>	<b><u>Ampule4</u></b>	<b><u>Ampule5</u></b>	<b><u>Aq. Sol'n</u></b>
<b>Boiling Pt.° C</b>	NA	185	100	78	100	>100
<b>Vapor Pressure mm Hg @ 21°C</b>	NA	0.5	18	44	18	16
<b>Solubility in Water</b>	reacts	75%	complete	miscible	miscible	complete
<b>Specific Gravity</b>	0.86	0.95	1.02	0.79	1.17	1.03
<b>Percent Volatile</b>	none	100	none	99	none	none
<b>Evaporation Rate Butyl Acetate =1</b>	NA	0.36	NA	2.7	NA	NA
<b>Appearance</b>	gray	colorless	colorless	red-green	colorless	colorless
<b>Odor</b>	none	ether-like	none	pleasant	NA	none

### **Section IV --- Fire and Explosion Hazard**

<b>Flash Point</b>	Ampule 1	212°F
	Ampule 2	162°F
	Ampule 3	NA
	Ampule 4	48°F
	Ampule 5	NA

**Flammable Limit** Unknown

**Extinguishing Media** DO NOT USE WATER ON A SODIUM FIRE. Dry chemical, foam, CO<sub>2</sub>.

**Special Fire Fighting Procedures** Do not use water. Wear SCBA. Avoid breathing sodium oxide fumes that will form on combustion.

### **Section V --- Reactivity Data**

**Stability** All components are stable.

**Incompatible With** Do not expose broken sodium ampule to moisture. Keep from strong oxidizers.

**Hazardous Decomposition Productions** Sodium will form hydrogen and sodium oxide when moisture is present. Diglyme may form peroxides on exposure to air. Other solutions are stable.

**Hazardous Polymerization** Will not occur.

**Conditions to Avoid** Moisture with sodium ampule.

## **Section VI --- Health Hazard Information**

### **First Aid**

In case of contact with reagents, rinse well with water. In case of inhalation, remove to fresh air.

### **Eye Contact**

For all kit components, flush eyes with large amounts of water for 15 minutes. Seek medical attention.

### **Skin contact**

Flush with large amounts of water. Use soap and water to wash away organic components.

### **Inhalation**

In case of inhalation, remove to fresh air.

### **Toxicological Information**

Harmful if inhaled or swallowed. May cause skin burns. Ingestion will cause burns of the gastrointestinal tract. Mercuric nitrate and ethanol (methanol component) are identified on lists in CERCLA, SARA Sec. 313 and on TSCA. Naphthalene is identified in the SARA Sec. 313 list.

## **Section VII --- Spill, Leak and Disposal Procedures**

### **Spills and Leaks**

#### *Ampule 1 - Sodium Ampule*

Cover with dry soda ash or salt. Store in a well-ventilated area away from moisture.

#### *Ampule 2 - Naphthalene/Diglyme Ampule*

Absorb completely and dispose of as organic waste.

#### *Ampule 3 - Mercuric Nitrate Ampule*

Absorb completely and flush area with water.

#### *Ampule 4 - Ethanol Ampule*

Solvent absorbent recommended for spills. Flush area with water.

#### *Ampule 5 - Disposal Ampule*

Absorb completely and flush area with water.

#### *Aqueous Solution*

Absorb completely and flush area with water.

### **Disposal**

#### *Pipette*

May contain residual PCBs, dispose of in accordance with all applicable federal, state and local environmental regulations.

#### *Test Tube 1*

Contents include reacted oil sample and organic liquid, and may contain residual PCBs. Dispose of as an organic waste in accordance with all applicable federal, state and local environmental regulations.

#### *Test Tube 2*

Upon completion of test including the addition of ampule 5, contents pass US EPA TCLP test. Dispose of in accordance with all applicable federal, state and local environmental regulations.

## **Section VIII --- Special Protection Information**

<b>Respiratory protection</b>	None required during normal use.
<b>Ventilation</b>	Perform test only in a well-ventilated area.
<b>Protective gloves</b>	Always wear rubber gloves when performing the CLOR-N-OIL test. Viton gloves are recommended for use with PCBs.
<b>Eye protection</b>	Wear safety glasses.
<b>Other protective equipment</b>	Wear appropriate safety equipment (electrical) when performing the test on site.

## **Section IX --- Special Precautions and Comments**

### **Storage and Handling Information**

Store test kits in a cool, dry place. Check expiration date prior to performing test.

**DOT Class** (As originally packaged by Dexsil Corporation.)

Approval CA-9610010, Packaging conforms to conditions and limitations specified in 49 CFR 173.4.

NA=Not available or not applicable

NF=Not found

NE=Not Established

The information in this Material Safety Data Sheet meets the requirements of the United States OCCUPATIONAL SAFETY AND HEALTH ACT and regulations promulgated thereunder (29 CFR 1910.1200 et. seq.) and the Canadian WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM. This document is intended only as a guide to the appropriate precautionary handling of the material by a person trained in, or supervised by a person trained in, chemical handling. The user is responsible for determining the precautions and danger of these chemicals for his or her particular application. Depending on usage, protective clothing including eye and face guards and respirators must be used to avoid contact with material or breathing chemical vapors/fumes.

Exposure to this product may have serious adverse health effects. These chemicals may interact with other substances. Since the potential uses are so varied, Dexsil cannot warn of all of the potential dangers of use or interaction with other chemicals or materials. Dexsil warrants that the chemicals meet the specifications set forth on the label.

DEXSIL DISCLAIMS ANY OTHER WARRANTIES, EXPRESSED OR IMPLIED WITH REGARD TO THE PRODUCT SUPPLIED HEREUNDER, ITS MERCHANTABILITY OR ITS FITNESS FOR A PARTICULAR PURPOSE.

The user should recognize that this product can cause severe injury and even death, especially if improperly handled or the known dangers of use are not heeded. READ ALL PRECAUTIONARY INFORMATION. As new documented general safety information becomes available, Dexsil will periodically revise this Material Safety Data Sheet.

CHEMTREC emergency telephone number is to be used ONLY in the event of CHEMICAL EMERGENCIES involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to the Customer Service Dept. at 1-203-288-3509.

*For additional information, contact Dexsil.*

Rev. 2,version2